LINEARlight FLEX

Tiras de LED flexibles de colores, recortable



Características del producto

- Puede dividirse hasta la unidad más pequeña o múltiplos de la misma sin afectar a la función del resto de la placa de circuitos impresos
- Regulable por modulación de impulso ancho (PWM)

Beneficios del producto

- Baja altura para montaje de superficie de perfil bajo/cerrado
- Baja carga térmica
- Posibilidad de montaje 3-D flexible
- Placa de circuitos impresos flexible con cinta adhesiva de dos lados para facilitar el montaje
- LF05A con dimensiones más reducidas y opciones de corte adicionales, gracias al uso de la tapa cierre LF-2TERM

Áreas de aplicación

- Inyección de luz en pantallas y guías de luz de perfil bajo
- Iluminación de señales informativas, de publicidad o para vitrinas
- Luz de fondo de contornos complejos
- Para aplicaciones decorativas: LF05A
- Pequeñas bóvedas y aplicaciones decorativas

© 2024, Inventronics GmbH. "Todos los derechos reservados. Inventronics es el titular de la licencia de la marca OSRAM. OSRAM es una marca comercial de ams OSRAM".

Hoja de datos gama de productos

Equipamiento / Accesorios

- Conexión simplificada con el sistema de conexión opcional CONNECTsystem

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.

© 2024, Inventronics GmbH. “Todos los derechos reservados. Inventronics es el titular de la licencia de la marca OSRAM. OSRAM es una marca comercial de ams OSRAM”.