

LFD400S -G2-940-10

LINEARlight FLEX Diffuse Side | – Módulos LED para aplicaciones profesionales e industriales

Características del producto

- Long operational length per single power feed up to 10 m



Beneficios del producto

- IP68 protection with high performance silicone
- Reliable connection over long periods of time: IP67 connector with built-in protection against liquids penetrating through the wires into the LED strip

Áreas de aplicación

- Iluminación de fondo para letreros de publicidad



Hoja de datos de producto

Datos técnicos


Datos eléctricos

Nivel de potencia nominal por metro	8,9 W
-------------------------------------	-------

Datos Fotométricos

Flujo luminoso por metro	390 lm
Desviación estándar de ajuste de color	≤3 sdc _m
Índice de reproducción cromática Ra	90

Dimensiones y peso



Peso del producto	190000 g
Largo	100000 mm
Ancho	141 mm
Alto	1080 mm

Datos adicionales del producto

ID of contained light source [AGGR]	LS_TRV_286443
-------------------------------------	---------------

Datos logísticos

Número estadístico de material	85395100000
--------------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	21-04-2023
Primary Article Identifier	4062172274197
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1

Hoja de datos de producto

Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	4ccfb56e-1d50-4a22-825a-c0e8f867f700

Texto de la hoja técni

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Descarga datos

Fichero	
	User instruction LINEARlight FLEX DIFFUSE
	Product Datasheet LINEARlight FLEX DIFFUSE Side_G2_Specification Sheet (EN)
	Folleto de ventas App Guide LINEARlight Flex Diffuse (EN)
	Folleto de ventas Light is freedom of design (EN)
	Certificados VDE ENEC CERTIFICATE 40052516 160823
	Certificados LINEARlight Flex DP UL 4413809 200622
	Eulumdat LFD400S-G2-965-10_ldt
	IES data LFD400S-G2-965-10_IES

Hoja de datos de producto

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Código del producto	Descripción del producto	Unidad de embalaje (Piezas/unidad)	Dimensiones (largo x ancho x alto)	Volúmen	Peso bruto
4062172274197	LFD400S -G2-940-10	Embalaje de envío 4	519 mm x 167 mm x 525 mm	45.50 dm ³	12480.00 g

El código del producto mencionado describe la unidad más pequeña de la cantidad que se puede pedir. Una unidad de envío puede contener uno o más productos individuales. Al cursar un pedido, introduzca la cantidad de la unidad de envío o su múltiple.

Accesorios Opcionales

Descripción del producto	Nombre de accesorio	Código de accesorio
LFD400S -G2-940-10	FX-LFDM -BEND-1000 KIT 3PCS	▶ 4062172192583

Aviso

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.