

FDS/DZE 64643 150W 24V 12/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54277		
Product Name	FDS/DZE 64643 150W 24V 12/CS 1/SKU		
Application	Projector, Microfilm, Microscope, Studio		
LIF Code	A1/262		
Product Remark	- s (Operating Position) = Vertical, base down		

Electrical data

Nominal Wattage	150 W
Nominal Voltage	24 V
Type of Current	AC

Light technical data

Luminous Flux	5000 lm
Light Center Length - LCL (in)	1.32 in
Light Center Length - LCL (mm)	33.5 mm
Color Temperature	3450 К
Color Rendering Index	100
Average Rated Life	100 h

Physical attributes

Base	GY9.5
Maximum Overall Length (in)	2.223 in
Maximum Overall Length (mm)	57 mm
Length l (in)	2.223 in
Length l (mm)	57 mm
Diameter d (in)	0.591 in
Diameter d (mm)	15.00 mm
Distance a (in)	1.320 in
Distance a (mm)	33.5 mm
Filament Dimensions Length (in)	0.1170 in
Filament Dimensions Length (mm)	3 mm
Filament Dimensions Width (in)	0.234 in
Filament Dimensions Width (mm)	6 mm

Additional product data

Operating Position	s 90

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54277	4008321099648	Folding box (SKU)	1	1.7 in x 1.7 in x 4.4 in	
54277	4008321099655	Shipping box (Case)	12	7.1 in x 5.5 in x 5 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.