

64602 50W 12V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54607
Product Name	64602 50W 12V 40/CS 1/SKU
Application	Projector, Microfilm, Microscope, Studio
LIF Code	M/134
Product Remark	– s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	50 W
Nominal Voltage	12 V
Type of Current	AC

Light technical data

Luminous Flux	1000 lm
Color Rendering Index	100
Average Rated Life	1100 h


Physical attributes

Base	G6.35
Maximum Overall Length (in)	1.716 in
Maximum Overall Length (mm)	44 mm
Length l (in)	1.716 in
Length l (mm)	44 mm
Diameter d (in)	0.472 in
Diameter d (mm)	12.00 mm
Distance a (in)	1.170 in
Distance a (mm)	30 mm
Filament Dimensions Length (in)	0.1170 in
Filament Dimensions Length (mm)	3 mm
Filament Dimensions Width (in)	0.117 in
Filament Dimensions Width (mm)	3 mm

Additional product data

Operating Position	s 90
Lamp Type	SINGLE END

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54607	4008321107077	Folding box (SKU)	1	1 in x 0.9 in x 2.8 in	
54607	4008321107084	Shipping box (Case)	40	5.9 in x 4.4 in x 4.6 in	1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.