

EJV 93637 150W 21V 24/CS 1/SKU



Características del producto

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Áreas de aplicación

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Datos técnicos

Información general del producto

NAED5 [AGGR]	54732
Description [AGGR]	EJV 93637 150W 21V 24/CS 1/SKU
Application	Projector - 8mm, Printer
Product Remark (US) [CRM]	– Lumens refers to screen lumens.

Datos eléctricos

Nominal Wattage [AGGR]	150 W
Nominal Voltage [AGGR]	21 V
Type of Current [CRM]	AC

Datos técnicos de iluminación

Lumens [AGGR]	270 lm
Working Distance a (in) [CRM]	1.486 in
Working Distance a (mm) [CRM]	38.1 mm
Color Rendering Index [AGGR]	100
Average Rated Life [AGGR]	100 h


Physical attributes

Base (OSI designation) [AGGR]	GX5.3
Bulb Shape [AGGR]	MR16
Maximum Overall Length - MOL (in) [CRM]	1.689 in
Maximum Overall Length - MOL (mm) [CRM]	43.3 mm
Length l (in) [CRM]	1.486 in
Length l (mm) [CRM]	38.1 mm
Length l max. (in) [CRM]	1.486 in
Length l max. (mm) [CRM]	38.1 mm
Diameter d (in) [CRM]	2.008 in
Diameter d (mm) [CRM]	51.00 mm
Filament [CRM]	CC-6

Datos adicionales del producto

Operating Position [CRM]	Any
Lamp Type [AGGR]	MR16

Hoja de datos de producto



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Peso bruto
54732	4050300350097	Estuche de cartón (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54732	4050300350103	Embalaje de envío (Case)	24	7.8 in x 5.2 in x 6 in	1.8 lb

El código del producto mencionado describe la unidad más pequeña de la cantidad que se puede pedir. Una unidad de envío puede contener uno o más productos individuales. Al cursar un pedido, introduzca la cantidad de la unidad de envío o su múltiple.

Aviso

OSRAM does not accept liability for errors, changes and omissions.