

64607 EFM 50W 8V 20/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54123
Product Name	64607 EFM 50W 8V 20/CS 1/SKU
Application	Projector - 8mm
LIF Code	A1/229
Product Remark	- p (Operating Position) = Horizontal

Electrical data

Nominal Wattage	50 W
Nominal Voltage	8 V
Type of Current	AC

Light technical data

Working Distance a (in)	1.260 in
Working Distance a (mm)	32 mm
Color Rendering Index	100
Average Rated Life	50 h


Physical attributes

Base	GZ6.35 BIPIN
Bulb Shape	MR16
Maximum Overall Length (in)	1.638 in
Maximum Overall Length (mm)	42 mm
Length l (in)	1.638 in
Length l (mm)	42 mm
Length l max. (in)	1.638 in
Length l max. (mm)	42 mm
Length l1 (in)	1.653 in
Length l1 max. (in)	1.653 in
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	C-8

Additional product data

Operating Position	p 90/15
--------------------	---------

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54123	4050300006789	Folding box (SKU)	1	1.8 in x 1.8 in x 2.3 in	0.1 lb
54123	4050300946399	Shipping box (Case)	20	9.4 in x 4.1 in x 4.8 in	1.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.