

ELC-3/X 250W 24V 24/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54841
Product Name	ELC-3/X 250W 24V 24/CS 1/SKU
Application	Overhead projection, fiber-optic, entertainment
LIF Code	A1/259
Product Remark	– Lumens refers to screen lumens.

Electrical data

Nominal Wattage	250 W
Nominal Voltage	24 V
Type of Current	AC

Light technical data

Luminous Flux	550 lm
Working Distance a (in)	1.238 in
Working Distance a (mm)	31.75 mm
Color Temperature	3250 K
Color Rendering Index	100
Average Rated Life	300 h


Physical attributes

Base	GX5.3
Bulb Shape	MR16
Maximum Overall Length (in)	1.765 in
Maximum Overall Length (mm)	44.83 mm
Length l (in)	1.765 in
Length l (mm)	44.83 mm
Length l max. (in)	1.765 in
Length l max. (mm)	44.83 mm
Diameter d (in)	39.366 in
Diameter d (mm)	999.90 mm
Filament	C8

Additional product data

Operating Position	Any
Lamp Type	MR16

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54841	4050300636450	Folding box (SKU)	1		
54841	10046135548410	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.