

## EXR 300W 82V 24/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54392
Product Name	EXR 300W 82V 24/CS 1/SKU
Application	Projector - Slide
Product Remark	- s (Operating Position) = Vertical, base down - Lumens refers to screen lumens.

Electrical data

Nominal Wattage	300 W
Nominal Voltage	82 V
Type of Current	AC

Light technical data

Luminous Flux	925 lm
Working Distance a (in)	5.948 in
Working Distance a (mm)	152.5 mm
Color Rendering Index	100
Average Rated Life	35 h

Physical attributes

Base	GX5.3
Bulb Shape	MR13
Maximum Overall Length (in)	1.755 in
Maximum Overall Length (mm)	45 mm
Length l (in)	1.755 in
Length l (mm)	45 mm
Length l max. (in)	1.755 in
Length l max. (mm)	45 mm
Diameter d (in)	39.366 in
Diameter d (mm)	999.90 mm
Filament	CC-8

Additional product data

Operating Position	s 90
Lamp Type	MR13

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54392	4050300350158	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54392	10046135543927	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.