

FLE 360W 82V 24/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54383
Product Name	FLE 360W 82V 24/CS 1/SKU
Application	Projector
Product Remark	<div>- Lamp service life 75hr life is defined at 76V with a duty cycle of 45 min. ON / 15 min. OFF. - Lumens refers to screen lumens.</div>

Electrical data

Nominal Wattage	360 W
Nominal Voltage	82 V
Type of Current	AC

Light technical data

Luminous Flux	1250 lm
Working Distance a (in)	1.190 in
Working Distance a (mm)	30.5 mm
Color Rendering Index	100
Average Rated Life	75 h

Physical attributes

Base	GY5.3 BIPIN
Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length l (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm

Additional product data

Operating Position	Any
Lamp Type	MR16

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54383	4062172146159	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54383	4062172146166	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.