

Hoja de datos gama de productos

OSRAM DULUX L LED HF

Lámparas especiales de LED



- Offices, public buildings Shops Hotels, restaurants
Industry Outdoor applications only in suitable luminaires

- Quick, simple and safe replacement Simple replacement thanks to similar design as conventional compact fluorescent lamps
Low energy consumption Operation directly on 230 V AC mains possible
- Caratteristiche prodotto LED replacement for conventional compact fluorescent lamps for use in ECG luminaires or on AC mains
Monoattacco a innesto a quattro pin 2G11 Lampada corta e compatta a due tubi (attacco a innesto) Grado di protezione: IP20 Durata: fino a 30.000 ore Lampade prive di mercurio Vantaggi prodotto Sostituzione semplice, veloce e sicura Sostituzione semplice grazie al design simile alle tradizionali lampade fluorescenti compatte Basso consumo di energia Possibile funzionamento direttamente su rete 230 V CA Aree applicative Uffici, edifici pubblici Negozi Hotel, ristoranti Industria Applicazioni outdoor sono negli apparecchi adatti

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany