

ICUTRONIC Intelligent – DALI (non-isolated)

Linear constant current LED driver – Dimmable



Áreas de aplicación

- Industry lighting
- Apto para luminarias con clase de protección I

Beneficios del producto

- Versatile non-isolated DALI driver up to 75 W due to flexible output characteristic
- Flexible current setting (RSet)
- High-quality dimming of 10...100 % by amplitude dimming
- No TouchDIM nor Corridor Function
- High quality of light thanks to <4% output ripple current
- Low standby power consumption: < 0.25 W

Características del producto

- Frecuencia de línea: 0 Hz | 50 Hz | 60 Hz
- Tensión de suministro: 220...240 V

Hoja de datos gama de productos

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.