

PrevaLED COIN 50 Tunable White

Módulos LED con óptica integrada y disipador de calor



Áreas de aplicación

- Comercios
- Restaurantes
- Hospitalidad
- Museos
- Gallery
- Apto para aplicaciones de interior

Beneficios del producto

- Compact form factor compatible with conventional MR16 CDM lamps
- Wide CCT range from 2700 K to 6500 K
- Targeting Human Centric Lighting (HCL)

Características del producto

- Color consistency < 3 SDCM in 2700 K
- High flux output up to 1,000 lm
- Beam angle: 24°, 40°

Hoja de datos gama de productos

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.