


PROFESSIONAL STARTERcable 900A



Hasta 900A de pico

Para transferir la corriente de carga para arrancar incluso baterías casi completamente descargadas



Hasta 7 litros

Adecuado para el arranque de vehículos con motor de gasolina o diesel con una capacidad de hasta 7,0L



450A amperios continuos

Para la transmisión permanente de la corriente y la protección contra el sobrecalentamiento, se da un amperaje continuo de 450A



Pure Copper

El cable está formado por conductores multifilares de cobre puro



Cables de arranque profesionales de OSRAM

With a range of OSRAM starter cables, motorcycle, car, commercial vehicle and truck drivers now have a quick and easy solution to rapidly transfer the battery power between a donor and a receiver vehicle and thus become ready to drive again. The OSRAM BATTERYstart PROFESSIONAL STARTER CABLE 900A is a high quality starter cable designed for professional and private use. The cables consist of multi-stranded conductors made of pure copper, which makes the resistance of the cable extremely low and enables a constant and effective transmission of the charge. The OSRAM BATTERYstart PROFESSIONAL STARTER CABLE 900A offers a high level of application safety thanks to the TÜV/GS-tested quality and is additionally CE-certified. The starter cable has a length of 4.5 meters with a cross-sectional area of 35mm². Thanks to the length and the cross-sectional area, it is possible to start vehicles with petrol and diesel engines with up to 7.0 liters of displacement, as a peak current strength of up to 900A can be achieved, at the same time a continuous amp rating of 450A is given. It is suitable for voltages of 12V and 24V. To prevent high wear and tear, the OSRAM BATTERYstart STARTER CABLE 900A is sheathed in flexible yet durable PVC, the insulated clamps and handles provide additional safety and durability. The different colors of the cables and the handles on the clamps reduce the risk of mixing up the positive and negative terminals and thus the risk of incorrect connection to the battery. The storage bag included in the scope of delivery allows the cables to be stored tidy and, in a space-saving manner. Conveniently, the operating instructions are also attached to the back of the storage bag and are thus quickly at hand. OSRAM offers a 2-year guarantee* on this product.

Hoja de datos gama de productos

Datos técnicos

Descripción del producto	Información de producto	Datos eléctricos		Dimensiones y peso	
	Engine type	Continuous amp rating	Pico de amperios	Longitud del cable	Largo
STARTERCable 900A	Diesel / Petrol	450 A	900A	4,5m	345 mm

Descripción del producto	Ancho	Engine size	Cross section area	Alto
STARTERCable 900A	225 mm	≤ 7.0L	35 mm ²	85 mm

Descripción del producto	Colores y materiales	Environmental information		
	Material	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
STARTERCable 900A	Copper	14-01-2022	4062172220934	In work

Hoja de datos gama de productos

Aviso legal

*consulte las condiciones exactas en:

www.osram.es/garantia-automovil

Consejos de aplicación: Para obtener información más detallada sobre la aplicación y los gráficos, consulte la hoja de datos del producto y el manual del usuario.

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.