

Basic Linear OP

Light Engine lineales



Características del producto

- Module efficacy: up to 140 lm/W
- Color temperature: 3,000 K, 4,000 K or 6,500 K
- LED module in 14 mm width, 489 mm length, Luminous flux on: 750 lm
- LED module in 14 mm width, 1095 mm length, Luminous flux on: 1500 lm
- Average lifetime (L80 B50): 35,000 h (temperature at Tc = 75 °C)
- CE, UKCA certified
- Índice de reproducción cromática R_a : 80
- For indoor application

Beneficios del producto

- Design for slim and flat luminaire fixture
- Wide range of light colors
- High homogeneity thanks to LED optical lens

Áreas de aplicación

- Office
- Hospitalidad
- Education
- Comercios
- Industria

Hoja de datos gama de productos

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Texto de la hoja técnica

- The LED module itself and all its components must not be stressed mechanically.
- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- The modules are intended for operation only with matching OPTOTRONIC , ICUTRONIC and ELEMENT.
- Pay attention to standard ESD precautions when installing the module.
- Max. Voltage U-OUT = 60V for operation on SELV LED control gear.
- The final luminaire assembled with modules must be well packaged with carton.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Referencias / links

* For more information on the multi-level guarantee and the terms and conditions of the guarantee visit <https://www.inventronics-light.com/multilevel-guarantees>

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.