

PrevaLED Linear QD

Light Engine lineales



Características del producto

- Lifetime (L85 B50): > 90,000 h (temperature at $T_p = 55\text{ }^{\circ}\text{C}$)
- Luminous flux: 280 lm on 62 mm
- Luminous flux: 570 lm on 124 mm
- Luminous flux: 1300 lm on 280 mm
- Luminous flux: 2600 lm on 560 mm
- CE and ENEC certified and UKCA marked
- Variation of color temperatures (3000K and 4000K)

Beneficios del producto

- Permite diseños de luminaria muy compactos
- Permite múltiples configuraciones del módulo en las luminarias
- Available with a wide range of lengths
- High efficacy LED Modules for CRI 90
- Small LED module design avoids shades, delivering great light uniformity
- Operativo con drivers OPTOTRONIC SELV y no SELV con y sin max. < 250 V
- Can be operated with OPTOTRONIC SELV drivers in the right configuration

Áreas de aplicación

- Industria
- Office
- Edificios públicos y comerciales
- Iluminación de comercios

Hoja de datos gama de productos

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.