


BoxLED M CP G5

Módulos LED para iluminación publicitaria y trasera



Características del producto

- Cadena de 32 módulos LED lineales
- Conectado con cables flexibles
- Maximum length of one chain: 9.80 m
- Tipo de protección (módulos): IP66
- Disipador de calor completamente integrado

Beneficios del producto

- Módulos compatibles con el perfil de montaje BackLED
- Iluminación homogénea gracias a las lentes elípticas optimizadas
- Varias opciones para un montaje rápido y sencillo: atornillar o encajar a presión
- Excelente eficacia de módulos
- Luz blanca consistente (desviación estándar de ajuste de color SDCM: 3)
- Vida útil muy larga
- 5 años de garantía

Hoja de datos gama de productos

Equipamiento / Accesorios

- Several types of OPTOTRONIC and ELEMENT 12 V power supplier
- BoxLED mounting profile BX-MP-M-CP-G5-2M
- BoxLED cable clip BX-CLIP-M-G5

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Soporte ventas y técnico

Soporte ventas y técnico www.osram.es

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.